



IP Monitoring Receiver (IPR512)

The Paradox IP Monitoring Receiver (IPR512) allows up to 512 supervised Paradox control panels (each with up to 32 sub accounts) to report system events over an IP network via Paradox reporting module (IP100 Internet Module or PCS100 GPRS Communicator Module). The IPR512 communicates with the monitoring station's Automation Software using Radionics 6500 format (other formats will be supported in the future). Paradox IP communication between panels and the IPR512 uses 256-bit AES data encryption. Each of the 512 accounts can be supervised at a configurable rate. With its minimal setup programming, easy account setup, low profile enclosure, SD card backup for fast data recovery and extremely low power consumption, the IPR512 is an excellent solution for today's monitoring station needs.

512 Supervised Paradox IP Modules

The IPR512 provides high-speed supervision for up to 512 Paradox control panels using a Paradox reporting module (IP100 or PCS100 GPRS). Each module can report up to 32 partitions, and each account can be supervised with one of the 32 customizable security profiles from UL-accepted high security to low security.

32 Security Profiles

Up to 32 security profiles can be created per receiver, each with a programmable Module Polling Time and Receiver Supervision Time (seconds, minutes, or hours). If the receiver does not receive a presence message from the Paradox reporting module within the Module Polling Time, the receiver will then wait until the Receiver Supervision Time elapses before reporting a supervision loss to the monitoring station's Automation Software.

Redundant Internet Service Provider

2 Ethernet ports (WAN1 and WAN2) to receive events through two different Internet Service Providers (ISPs).

2 Serial Ports

COM1: connects to Automation Software (used by monitoring station) by emulating Radionics 6500 protocol (more formats to be added latter).

COM2: connects to a serial printer and/or PC with RS232 serial communication software to view/print events in plain text format.

Integrated Account Management Web Page

The receiver's Account Management web page interface can be accessed through the LAN port. The Web page interface is used for all Receiver programming as well as to add/remove Paradox reporting modules.

Data Backup on External Memory Card

The receiver has a built-in flash memory card slot for automatic data backup (programmable intervals) and recovery. This allows fast and easy substitution of receiver when needed. Uses external 1GB SD card.

Firmware Upgradeable

The receiver is firmware upgradeable within a few minutes via the IP connection and features automatic update verification.

Other Features


- Supports CID and SIA reporting formats
- 256-bit AES data encryption
- Supports 19" standard rack mounting (1U) or desktop installation
- Output relay (triggered by selected events)
- Input relay (sends selected events when triggered)
- Automatic date and time synchronization via Network Time Protocol (NTP)
- Robust and durable construction
- Standard 110/220Vac power supply
- No noise operation and low power consumption (under 10W)
- Secure private operating system

512 Supervised IP Modules with Automatic Registration

The IPR512 provides high-speed supervision for up to 512 Paradox control panels using a Paradox reporting module (IP100 Internet Module or PCS100 Communicator Module - GPRS edition). Each module can report multiple partitions. For example, the receiver can support 512 Digiplex EVO control panels, each reporting 8 partitions. Therefore the receiver can supervise all 4096 accounts (512 x 8). No monitoring station operator action is required to register a Paradox reporting module. The installer registers the module by entering the account #, IP Address, Port #, and security profile in the control panel. When the installer initiates communication with the receiver, the Paradox reporting module accounts are created automatically in the receiver.

How Does It Work?

The following is a basic overview of the event reporting transmission path (control panel to automation software).



1. Due to its proprietary serial port communication, the control panel can report through a landline and an IP network.
2. The Paradox reporting module connected on the serial port of the control panel encrypts the reported events using 256-bit AES. The encrypted events are then sent through the Internet to WAN port of the receiver defined by the IP address set in the control panel. The entire process takes only a few seconds.
3. The reported events are decrypted by the receiver, which supports both CID and SIA formats. The receiver provides a redundancy option with its two on-board WAN ports, which enables it to receive events through two different Internet Service Providers (ISPs).
4. Reported events are converted to the Radionics 6500 protocol (Bosch D6600) and sent to the Automation Software through COM1.
5. Reported events are also sent in plain text format through COM2, which can be printed or viewed using a PC running RS232 serial communication software.

Firmware Upgradeable

The receiver is firmware upgradeable and features automatic update verification. The receiver will periodically check online if there are any new updates. If a new update is available it will appear in the Web Page Interface. Once you confirm the update, the receiver will be up and running with the new update within a few minutes.

Fail Recovery Features

The receiver offers many features to ensure that the report codes are sent to the automation software and to ensure fast crash recovery.

Redundant ISP (Internet Service Provider)

Each receiver features two WAN ports each with a programmable IP address allowing it to receive events through two different Internet Service Providers (ISP). Each control panel can be programmed to report to both WAN ports. If there is a problem with the ISP network, reports can still be reported through another ISP.

Memory Card

The receiver has a built-in flash memory card slot. Insert an external SD, SD/HC, or MMC memory card for data backup and recovery. Stored data includes the unit's configuration settings and all account information. Data backups occur at programmable intervals or can be done manually through the LCD and 6-Button Interface. The last 10 backups are kept on the memory card. This allows fast and easy substitution of receiver units in crash recovery situations. Simply remove the memory card, insert the card into another receiver, load data from the memory card, and you're up and running in just a few minutes. 1G SD Memory card included.

Receiver Secondary Serial Port


Reported events are also sent in plain text format through COM2, which can be printed or viewed using a PC running RS232 serial communication software. Gender changer included.

Control Panel Isolated Serial Port

The Paradox reporting module is connected to the Paradox control panel's isolated serial port. If the control panel's AUX output fails (short/overload), the module will continue to operate.

End-to-End Supervision


The following describes how end-to-end supervision is achieved with Paradox's proprietary communication between control panel, communication module and receiver.




1. The control panel supervises the presence of the Paradox reporting module. If communication is lost, the control panel will generate a trouble and can report the trouble through a landline, GSM, or SMS.
2. The Paradox reporting module supervises the presence of the control panel. If communication is lost, the module will report the trouble to the receiver and can send an e-mail.
3. The Paradox reporting module also supervises the Ethernet connection. If connection is lost, the control panel will generate a trouble and can report the trouble through landline, GSM or SMS.
4. The receiver supervises the presence of the 512 assigned Paradox reporting modules. Up to 32 security profiles can be created per receiver with a programmable polling time (seconds, minutes, or hours). These profiles are then assigned to each module during registration. The module will send a presence message (~100 bytes) at intervals defined by the security profile. To avoid false alarms, the receiver also features a programmable grace period per security profile. If the receiver does not receive the presence message at the required interval, the receiver will wait until the programmed grace period elapses before reporting a communication loss.
5. The receiver supervises the Ethernet (WAN) connections. If the connection is lost, the receiver displays a trouble and then can report it to the automation software.
6. The receiver supervises communication with the automation software using the ACK/NACK protocol. If communication is lost, the receiver will save all incoming events (up to 10,000). When communication is restored, the receiver will send the saved events to the automation software. The receiver will also display a trouble and can also activate its output relay (e.g. turn on a warning light).

Account Management Web Page


A web page is integrated into the IP Monitoring Receiver (IPR512) and can be accessed through its LAN port using an Internet browser.




- Configure the receiver (WAN1, WAN2, LAN, COM1, COM2, ID, Line, and Date/Time)
- Register the unit and upgrade its firmware
- View, edit and delete up to 512 registered Paradox reporting modules
- Setup 32 security profiles (poll time and grace period)
- View receiver status including any occurring troubles
- Define which account-related events or receiver-related events will be reported to the automation software and/or will activate the receiver's output relay
- View and restore up to 50 deleted reporting modules
- Set time and date manually with optional daylight savings time or select Network Time Protocol (NTP) for automatic time and date synchronization



Front Panel Overview



Back Panel Overview



Input Trigger

Used to generate an event that can be reported to the automation software and/or activate the output relay.

Output Relay

Used to activate an external device, such as a warning light, when an account-related event (i.e. IP Module Supervision Loss) or receiver-related event (i.e. communication trouble) occurs. The PGM will turn off when the event is restored or when acknowledged on the LCD. Event selection is programmed via the receiver's internal web page.

COM1 (Automation Software)

Dedicated port for automation software. This output can be supervised through the ACK/NACK protocol. The receiver is compatible with any automation software compatible with the Radionics 6500 standard (Bosch D6600). 10-foot DB25 to DB9 cable included.

COM2 (Printer/PC)

Reported events are also sent in plain text format through COM2, which can be printed on a serial printer or viewed using RS232 serial communication software. Gender changer included.

LAN (Web Page Interface)

A web page interface is integrated into the IP Monitoring Receiver (IPR512) and can be accessed through its LAN port ("Account Management Web Page" on page 3).

WAN1 / WAN2 (ISP)

Each receiver features two WAN ports each with a programmable IP address allowing to receive events through two different Internet Service Providers (ISPs).

Power Input

Built-in 5A power supply using standard 110/220Vac (50/60Hz) power input. Low power consumption (less than 10W) and noiseless operation. 6-foot AC power cord included with choice of plug (Australia, China, Europe, North America, and UK).

P R D X®
S E C U R I T Y S Y S T E M S

PARADOX.COM
TIPR-G2K rev02 10/2008